



DE-GEL SUPREME

- **QUICK-ACTING**
- **LIQUIFIES GELLED FUEL**
- **DE-ICES FROZEN FUEL FILTERS AND LINES**
- **100% SAFE FOR FUEL SYSTEMS**
- **EASY TO USE**

DE-GEL SUPREME Quick-Acting

When temperatures drop and diesel fuel begins to gel, problems start to rapidly develop. A sudden, unexpected temperature drop can cause the wax in diesel fuel to solidify and gel. Even the best maintained equipment can be brought to a halt by gelled diesel fuel.

DE-GEL SUPREME Liquifies Gelled Fuel

DE-GEL SUPREME is highly concentrated and designed to quickly dissolve wax in fuel filters, fuel lines and fuel tanks. Within minutes DE-GEL SUPREME liquifies gelled diesel fuels. This eliminates the need for costly tow trucks. DE-GEL SUPREME contains ingredients that are soluble in both petroleum and water.

DE-GEL SUPREME De-Ices Fuel Filters and Lines

In addition to dissolving wax, DE-GEL SUPREME is specially formulated to quickly dissolve ice build-up in fuel filters, fuel lines and fuel tanks. It is a de-gel and de-icer all in one.

DE-GEL SUPREME Safe For Fuel Systems

While there are a variety of products on the market, many contain harmful methanol or



DE-GEL SUPREME gets you back on the road by quickly liquifying gelled diesel fuel.

ethanol type products. Methanol and ethanol type products can cause serious rust and corrosion problems within the fuel system.

Other products can also affect the flash point of a #2 diesel fuel by lowering the flash point. In fact, there are some products which can drastically affect start-up. DE-GEL SUPREME is the ultimate package. While quickly acting to dissipate fuel and melt ice, it is 100% safe for the system and allows fuel to burn at peak efficiency.

DE-GEL SUPREME Easy To Use

DE-GEL SUPREME is exceptionally easy to use. A little bit of this highly concentrated product goes a long way in getting downed equipment back on the road. It is safe for use in diesel or kerosene blends. It is exceptionally beneficial in removing moisture in tanks and preventing further icing once you have de-gelled fuel.

DE-GEL SUPREME quickly and efficiently opens fuel lines and filters blocked by ice and wax. Because of its quick-acting efficiency, downtime in cold weather is drastically reduced. No need to call the tow truck when you have an emergency diesel fuel treatment with DE-GEL SUPREME.

INSTRUCTIONS FOR EMERGENCY TREATMENT

1. Remove fuel filter.
2. Drain any and all remaining liquid from filter.
3. Add DE-GEL SUPREME to fuel filter receptacle until full.
4. Reinstall fuel filter.
5. DE-GEL SUPREME must be added to equipment fuel tanks at the ratio of 1 litre to 100 litres. (Less severe situations can use a ratio of 1 litre of DE-GEL SUPREME to every 200 litres of fuel.)
6. Wait 15 minutes to allow DE-GEL SUPREME to work before starting engine. If engine is sluggish or will not start, wait another 15 minutes.
7. Start engine and let idle 5 minutes before returning to full operation.
8. As a preventive maintenance to prevent such roadside emergency, winterize your fuel with DZL-PEP ARCTIC manufactured by Texas Refinery Corp.

DE-GEL SUPREME is registered with EPA per 40 CFR 79.23
Registration Number: 0285-0010

SPECIFICATIONS

DE-GEL SUPREME

Product Code: #6380

API Gravity @ 15°C

30

Flash Point, °F./°C

95/35

Handling Information: For safe handling of the product, read the Safety Data Sheet (SDS).



CANADA

TEXAS • ONTARIO • SASKATCHEWAN

Phone: 800-827-0711 • www.texasrefinery.ca

PRINTED 10/2015